| | |
|---|---|
| Temperature range* | 10°C to 40°C |
| %RH (optional)* | 50% to 90% RH as limited by dew points |
| Temperature uniformity | ± 1°C |
| % RH control (optional) | ± 3% |
| Temperature control at sensor | ± 0.2°C |
| Control resolution | ± 0.1°C |
| Cooling/Heating type | Thermoelectric/Peltier driven-for heating/Cooling |
| Chamber Volume in Cu. Ft | 68 cu.ft |
| External Dimension-LXWXH | 81″×31.5″×81″-86" (refer to drawing) (Note chamber can be tilted while installing through standard door ways) |
| Internal Dimension-LXWXH | 77″ x 25.25″ x 60″ (refer to drawing)- height includes plenum which is 5″H. |
| Shelf dimension | 23"x 24" |
| Cabinet specs | Stainless interior and corrosion resistant painted black steel exterior construction |
| Lights | LED lights with diurnal programmable timer. |
| Electrical requirement | 115V/60hz/1ph/15a, Unit plugs into standard wall outlet. |
| Shelf quantity, type | 12 per chamber/ additional shelves available, wire shelf- PVC coated with 4 installation clips. Shelf capacity- 100 lbs distributed load. |
| Weight specs | Chamber weight- 673 lbs<br>Shipping weight- 781 lbs |

*Specifications are based on 20°C ambient and standard voltage. Specifications are subject to change without notice.

**Chamber options:**

- Chart recorder
- Additional shelving
- Relative humidity
- Extended temperature ranges
- RO/DI water filtration system
- Water carboy

**Chamber features:**
This chamber is used by scientists in many research areas, from genomics to clinical epidemiology and species conservation. This chamber not only can be used in drosophila research but also in many types of insect growing projects as well.
All of the Canden chambers interior are made out of premium stainless steel. Chamber has 2” thick CFC free insulation providing good thermal gradient. Door locks are standard in doors with double pane glass. Chambers comes with 2” access port with insulation plug. Chamber also includes pre-installed casters capable of supporting 150-200lbs per caster. **Chamber can hold up to 75 shelves.**

Chamber uses thermoelectric assembly for heating and cooling. This type of cooling/heating system completely eliminates need for conventional refrigeration system and failures due to mechanical components such as compressors thereby drastically increasing the life expectancy of each chamber. Maintenance cost is also lowered by the thermoelectric/Peltier driven heating/cooling system. The chamber is quiet in operation. Back wall plenum on chambers ensures uniform distribution of conditioned air. Chamber temperature set points are tightly controlled using programmable Fuji or watlow model PID controller.

Chamber standard features also include **industry standard programmable grasslin light timer or equivalent**. Chamber has 6-3' led lights Natural 5500k,1080 lumens each,3.4 watts per ft. Customer specified led lights can be added at no cost.

Humidity system: Humidity control is optional. Humidity range is achieved via additive ultrasonic humidification, a controller with with factory calibrated %RH sensor. Humidifier is installed typically in the rear of the chamber and can be easily serviced or replaced. RO/DI system is recommended but not required as long as the water quality specification is met. Tap water should be fine. The humidifier comes with a 15’ ¼” polytube, shut off valve and quick disconnect fittings as well as a fitting to connect to water faucet.

Water quality specification:
Water conductivity greater then 0.1 µS,TDS of < 10 ppm and works in operating pressure range from 10psi to 80 psi"

# Insect growth chamber Specification

**Model No: IRCGDM3**

some chamber may
need 5" extra
height for humidifier







*Interior Dimensions

SELF-CLOSING
AND STAY OPEN
DOOR FEATURE

Canden Products
St. Louis, Mo

Email: sales@candenproducts.com