Temperature range*	18°C to 50°C Ext temp range 10c to 70c
%RH (optional)*	50% to 80% RH Ext %RH range 20% to 90%RH
Temperature uniformity	± 1°C
% RH control	± 3%
Temperature control at sensor	± 0.2°C
Control resolution	± 0.1°C
Cooling/Heating type	Thermoelectric/Peltier driven-for heating/Cooling
Chamber Volume in Cu. Ft	19.1 cu.ft
External Dimension-LXWXH	27″×31″×81″ (refer to drawing for standard and optional unit dimensions)
Internal Dimension-LXWXH	22.25″ x 25.25″ x 60″ (refer to drawing)- height includes plenum which is 5″H.
Shelf dimension	21.75” x 24.875”
Cabinet specs	Standard: SS exterior/aluminum interior. Optional: Black painted exterior/SS interior
Lights	LED lights with timer.
Electrical requirement	115V/60hz/1ph, Unit plugs into standard wall outlet.
Shelf quantity, type	3 per chamber/ additional shelves available, wire shelf- PVC coated with 4 installation clips. Shelf capacity- 100 lbs distributed load.
Weight specs	Chamber weight- 293bs Shipping weight- 326 lbs

*Specifications are based on 20°C ambient and standard voltage. Specifications are subject to change without notice.

Chamber options:

- Chart recorder
- Additional shelving
- Relative humidity
- Extended temperature ranges
- Carboy
- 2" Access port

Chamber features:
Canden stability chamber with glass door front is capable of maintaining stable temperature across wide operating temperature range of 18°c to 50°c and relative humidity range of 50% to 80% as limited by operational dew points and ambient condition. This chamber provides outstanding stability testing performance for manufacturers of pharmaceuticals, biologics, food, and personal care products. Canden stability chambers' performance meets ICH Q1A general case guidelines for pharmaceutical stability testing. Chamber is designed with upper plenum with front to back airflow system for uniform sample exposure. Door locks are standard in doors. Chamber uses thermoelectric assembly for heating and cooling. This type of cooling/heating system completely eliminates need for conventional refrigeration system and failures due to mechanical components such as compressors thereby drastically increasing the life expectancy of each chamber. Back wall plenum on chambers ensures uniform distribution of conditioned air. Chamber temperature setpoints are tightly controlled using PID controller. Fuji controller is standard. Watlow 4T-Touchscreen controller is also available.
Humidity system: Humidity control is optional. Humidity range is achieved via additive ultrasonic humidification, a controller with with factory calibrated %RH sensor. Humidifier is installe
easily serviced or replaced. RO/DI system is recommended but not required as long as the water quality specification is met. Tap water should be fine. The humidifier comes with a 15' 1/2" " polytube, shut off valve and quick disconnect fittings as well as a fitting to connect to water faucet.
Water quality specification:
Water conductivity greater then 0.1 µS,TDS of < 10 ppm and works in operating pressure range from 5 to 10psi"



Black painted exterior/SS interior--option 1

Standard: Stainless steel exterior and Aluminum interior-Option 2

Plan View



Front View



Side View



Top View